



LEGEND

SYMBOL	DESCRIPTION
[Symbol]	USE THE MANUFACTURER'S AND THE MANUFACTURER'S 150 AMP 600 V 2 YC
[Symbol]	REVISION DATE
[Symbol]	REMARKS
[Symbol]	MINIMUM CIRCUIT BREAKER
[Symbol]	MINIMUM PROTECTION CIRCUIT BREAKER
[Symbol]	CURRENT TRANSFORMER
[Symbol]	100 TYPE PHASE INDICATOR LIGHTS
[Symbol]	100 TYPE 6A, 100 AMP INCANDESCENT LIGHTS
[Symbol]	100 TYPE 6A, 100 AMP INCANDESCENT LIGHTS
[Symbol]	100 TYPE 6A, 100 AMP INCANDESCENT LIGHTS
[Symbol]	100 TYPE 6A, 100 AMP INCANDESCENT LIGHTS
[Symbol]	100 TYPE 6A, 100 AMP INCANDESCENT LIGHTS
[Symbol]	100 TYPE 6A, 100 AMP INCANDESCENT LIGHTS
[Symbol]	100 TYPE 6A, 100 AMP INCANDESCENT LIGHTS
[Symbol]	100 TYPE 6A, 100 AMP INCANDESCENT LIGHTS
[Symbol]	100 TYPE 6A, 100 AMP INCANDESCENT LIGHTS
[Symbol]	100 TYPE 6A, 100 AMP INCANDESCENT LIGHTS
[Symbol]	100 TYPE 6A, 100 AMP INCANDESCENT LIGHTS
[Symbol]	100 TYPE 6A, 100 AMP INCANDESCENT LIGHTS

EL.SCH.--.01

R1

project IIA HOSKOTE

sid layout